

SABRE 52 SALON EXPRESS

2008 MODEL YEAR SPECIFICATION

Length (without anchor pulpit or swim platform)	53'2"	16.37 m	
LOA (swim platform to bow roller)	58' 0"		
LWL	49'-3"	15.15 m	
Beam (overall)	16'-0"	4.92 m	
Draft	4'-3"	1.30 m	
Height from waterline to top of hardtop		11'5"	3.5 m
Deadrise (at transom)	15 degrees		
Displacement (approx., EST dry)	46,000 lbs.	20865 kg	
Fuel capacity	800 gal.	3028 l	
Estimated Range at 27-28 knot cruise approx 58 gph	340 nm		
Water capacity	200 gal.	757 l	
Holding tank capacity	80 gal.	302 l	
Headroom (maximum)	6'-6"	2.00 m	
Sleeping accommodations	6/6'-8"	4/ 2.03m	

Built to CE Category B, NMMA, ABYC and USCG standards

PROPULSION SYSTEM

- Twin diesel CAT C15 865 mhp
- Fresh water-cooled
- Twin Disc QUICKSHIFT Transmission MGX 5114A
- Twin Disc EC300 Electronic controls w/ Express Mode (required to maximize Quickshift features)
- 2 3/4" stainless steel shaft (Aquamet 22 or equivalent)
- PSS drip-less shaft seals
- Manganese bronze struts with cutlass bearing
- NiBrAl four blade propellers to ISO Class S
- 24V alternators each engine
- Seawater cooled 10" underwater transom corner exhaust system
- Groco raw water intake strainers
- Oil change system for engines and gen sets
- Engine room ventilation system 24v
- Engine room intake ducts on cabin house side with stainless steel grill
- White gelcoated engine room
- White Mylar faced foam noise 2# barrier

HULL COMPOSITE

- Modified "V" planing hull design with shallow prop pockets.
- 23 degree deadrise amidships and 15 degree deadrise at transom
- Reverse sloped transom
- ISO NPG Sport Yacht white gel coat w/ vinylester back-up resin
- Knitted Biaxial Structural E-Glass Reinforcements
- Vacuum Bagged Airex PVC foam core in hull bottom (1.5") and Topsides (1/2")
- PVC Foam and Airex cored composite stringer system
- Swim platform with under-mounted telescoping ladder
- Hull side rubbing strakes
- PVC rub rail with stainless steel cap
- Painted (IMRON) Double Boot Strip
- Gold Cove Stripe

DECK AND HARDTOP COMPOSITE

- ISO NPG gelcoat
- Knitted Biaxial Structural E-Glass Reinforcements with foam coring
- Molded in anti-skid deck surfaces
- Recessed salon windows with clear anodized frames

- Hardtop with integrated electric sliding sunroof and shade
- Custom Sabre composite radar mast mounted on spray hood
- (2) Double sided anchor locker w/Southco slam latch
- (3) Large double sided lazarette locker hatches with gas struts and Southco 3" dia. compression latches
- (1) Access hatch from aft cockpit to engine room with electric lift
- Aft facing bench in aft cockpit
- Forward facing transom seat with storage below

DECK HARDWARE

- 1 1/2" diameter type 316 stainless steel perimeter rail system
- (4) stainless steel spring cleats
- (2) stainless steel mooring cleats
- (2) stainless steel stern cleats
- Custom stainless steel dual anchor roller
- 24V Electric Windlass with controls at helm and foot switches on deck (Lewmar V4)
- Flagpole holder and flagstaff
- Lewmar Low Profile polished aluminum hatches w/screens
- Oversized Stainless steel opening ports
- Teak toe rails port and starboard with custom cast dual mid rail chocks and bow chocks
- Teak cabin side eye-brow
- Custom cast stainless steel "SABRE" medallion
- Cast stainless steel corner hawse pipes in cockpit through hull sides and transom

FUEL SYSTEM

- 800 gal diesel fuel. (2-400 gallon tanks)
- Exterior of tank coated with corrosion barrier
- Racor dual Max 1000 fuel filters
- Walker engineering Algaesep fuel polishing system to maximize fuel performance
- 2" "Diesel" stainless steel deck fill plate
- Fuel Level Indicator at helm

STEERING SYSTEM

- Power assisted hydraulic steering
- Twin Bronze rudders
- Twin Electro Tab trim tabs
- Bow Thruster (Side-Power SP 155)

240/120 VAC ELECTRICAL SYSTEM

- Dual 240/120 VAC 50 amp AC shore power systems
- One 75 ft. Glendinning Cord Reels
- One 240V bow inlet
- Dual 9.0kW Onan Generators with sound enclosures
- Dual 12KVA isolation transformers
- Automatic AC master switching system for shore & generator power
- 4kW high output inverter with 120 Amp DC Charger for ships batteries
- Main circuit breaker distribution panel in engine room
- 240V outlets in each cabin and one in engine room
- All galley and head receptacles are GFI protected
- Professional Mariner 25 Amp, 3-bank battery charger for engine & generator batteries
- Reverse Cycle Air Conditioning

24 VDC ELECTRICAL DISTRIBUTION SYSTEM

- Dedicated engine starting battery bank
- Dedicated 24v 8D AGM deep cycle ship's service batteries
- Helm remote controlled battery switches with manual override
- 12V DC System available for helm electronics
- Main circuit breaker distribution panel w/battery condition gauge
- Multiple 12v outlets at helm and in interior for small personal appliances, phones, etc.
- Tinned marine grade wire throughout
- Air Horn, Kahlenberg™
- Navigation lights

- Triple wiper/washer system
- Lighting:
 - Danish Cabin reading lights
 - I2Systems High output LED lights in the overhead
 - Halogen bar lighting in appropriate locations
 - Engine room lighting
 - Cockpit courtesy lights w/remote switch at transom door

WASTE DISPOSAL

- (1) Polyethylene holding tank with 80 gallon capacity
- Freshwater MSD's with white ceramic bowls
- Macerator pump on holding tank to overboard sea valve
- Integrated gray water holding with macerator pump out and back-up overflow pump
- Waste & gray water tank level monitor at helm

FRESH WATER SYSTEM

- Water capacity approx. 200 gals.
- 20 gal. 240V hot water heater with heat exchanger
- Dual 24VDC pumps on hot and cold water pressure system
- Fresh water coil hose in engine room
- Fresh water wash down spigot at anchor locker
- Salt water wash down at anchor locker w/ coil hose

MAIN SALON / HELM AREA

- Twin Stidd helm seats on pedestals at helm position
- Pantograph style door to side deck from helm
- Stainless steel sliding door to aft cockpit with curved windows on corners
- Helm dash area finished in cherry
- Navigation switch panel
- Flat chart area to port of engine control panel
- Custom wood trimmed stainless steel wheel
- Recessed sub AC/DC breaker panels facing aft helm bulkhead
- Raised "Mates Lounge" to port with Ice Maker below and chart storage
- Oversized U-shaped lounge with custom fabrics. Converts to sleeping berth, drawers below and storage for removable table center leaf
- Fixed height pedestal table with starburst inlay and deep epoxy finish and add-on leaf
- Entertainment cabinet to include LCD TV w/ Bose 3.2.1 stereo/DVD player
- Cabinet aft of helm seats with bottle storage, stem ware storage and wine chiller
- Barrel chair
- Blinds and curtains on all windows
- Teak and holly sole with (2) coats of sealer
- Sound deadening headliner panels
- Electrically operated sun roof over main salon
- Air Conditioning (2) x (16000BTU)

GUEST STATEROOM- Forward

- Spacious low queen island berth layout with 5" mattress. ¾" laminated trim.
- Ash hull ceilings
- 2 Drawers under bed. A/C return grills under drawers
- Aft end of berth top hinges open to access blanket storage
- Enclosed upper shelves to port and starboard of island berth with storage behind. Fwd most section (about 24") to be open shelf w/fiddle. Locker face to have two solid doors each side. Each door to access partitioned space with shelves in the aft two compartments. Locker doors to be hinged at top.
- Large cedar lined hanging locker to port with cedar shelf and closet pole. Open shelf above
- Bureau to starboard with enclosed locker above
- Built in LCD TV on forward facing bulkhead with DVD player
- Shade for hatch
- Private access to guest head/shower compartment
- Teak and holly sole with 2 coats of sealer
- Soft headliner panels
- Pocket door

- Air Conditioning (9000 BTU)

GUEST/DAY HEAD- Forward

- Stainless sink with faucet
- Separate shower stall with circular door
- Ceramic tile floor in WC compartment
- Hot and cold pressure water
- Storage lockers
- Soap dispenser in counter
- Solid surface counter with bull nose
- Teak shower grate
- Stainless steel towel bars
- Wood trimmed mirror over sink and mirror in top of passageway door (head side)
- Ventilation blower

GALLEY

- Extra Large galley with two oversized port lights in cabin side
- Fixed port light in hull above the counter
- Toe kick space length of galley with courtesy lighting
- Galley area with Viatera Quartz countertop. Bull nosed edge overhangs cabinet below
- Electric 3 Burner stove top
- Convection microwave oven
- 240VAC galley exhaust fan
- Large storage drawer below oven
- Bulkhead cabinet above oven on wall facing aft
- (2) Zub-Zero Stainless Steel 700BC 240 v Combo Fridge/ Freezer Drawer Units. Each unit has 3 cubic ft. of refrigeration and 2 cubic ft. of freezer space (6.0/4.0 cu. ft total storage volume in 4 drawers). One unit located under galley and second unit locate opposite galley forward of pantry
- Fischer & Paykel DishDrawer dishwasher w/ cherry front
- Coffee maker with integral water supply
- Bank of drawers aft of sink
- Stainless steel under-mounted double bowl sink mounted below counter
- Storage cabinet below sink with shelf and double doors
- Above counter storage outboard
- Pantry cabinet opposite galley runs floor to ceiling with deep adjustable shelves and waste basket
- Vented washer dryer unit above fridge in hallway forward of pantry
- Additional storage beneath stairs
- Galley air conditioning (9000 BTU)

MASTER STATEROOM and HEAD – Amidships

- Double Shoji style pocket doors lead to the large master suite (approx. 48" total opening)
- Spacious low queen island berth layout with 6" mattress. ¾" laminated trim
- Base of bed to incorporate drawers and storage
- Bureau/night stand with drawers to each side of bed, bookshelf above headboard
- Cedar lined hanging lockers with cedar shelf and closet pole. Open shelf above.
- High Boy style dresser with four drawers
- Built in LCD TV with DVD player
- Shades for all ports and hatches
- Exclusive access to master head/oversized shower compartment through pocket doorway
- Full length mirror behind pocket door from hallway
- Teak and holly sole with 2 coats of sealer
- Stateroom air Conditioning (9,000BTU)
- Soft headliner panels.
- Designer sink with faucet.
- Separate shower stall with vent fan
- Electric shower sump pump
- Storage lockers
- Soap dispenser in counter
- Cherry counter with bull nose
- Ceramic tile on head compartment and shower floor

- Stainless steel towel bars
- Wood trimmed mirror over sink
- Ventilation blower

DÉCOR

- Screens and shades on all opening ports and hatches
- Optional fabric and drapery selections
- Custom décor packages available
- Dovetailed maple drawer boxes throughout

MAJOR OPTIONS AVAILABLE

- Teak aft Cockpit sole
- Teak coaming caps
- Teak inlay on swim platform
- Dark hull colors
- Dinghy lift system

SAFETY

- Fire extinguishers, (5) at 2 1/2 lbs.
- Marelon sea valves on all below waterline fittings.
- Bonding system to safeguard against galvanic corrosion
- Automatic fire extinguishing discharge system with override
- (3) Automatic electric bilge pumps
- (3) Bilge high water alarms

These specifications are subject to change without notice.

Revised December 2007